

FII 3.0

Multimodal Biometric Device



- **Simultaneous capture of both irises and the face (fingerprint optional)**
- **Most cost and time efficient way to collect high quality biometric data**
- **Manual adjustable, handheld mobile and wall-mounted versions are available**
- **Large range of operation (2 feet) and capture volume (1.5 cubic feet)**
- **Large covered height difference (3'6" to 7'8")**
- **Unaffected by ambient lighting**
- **High tolerance to motion (up to 0.7m/s)**
- **Built in anti-spoofing capabilities**
- **Flexible interfaces and 3rd party integration**



Technical Specification

Dimensions (W x H x D)	5.52" x 2.36" x 3.72" (140mm x 60mm x 95mm)
Weight	13.5oz (0.38kg) – main unit
Power Management	12V AC Adapter included
Operating System	Windows XP or above (external)
Database	Flexible choice of SQLite, MySQL, Sybase, Oracle, or DB2 (external)
Connectivity	USB 2.0 Client 1 Port
Operating Range	8" – 32" (20.3cm – 81.3cm)
Capture Volume	1.5 cubic feet, with manual rotation ~7.5 cubic feet
Optimal Distance	20" (50.8cm)
Motion Sensitivity	Can tolerate up to 0.7m/s head movements
Rotation Angle	+65°/-65° manual rotation
Covered Height	3'6" to 7'8"
Operational Mode	Simultaneous capture of both irises and the face (fingerprint optional)
Capture Time	Less than 1 second
Matching	Default or pluggable iris and face algorithms
Match Time	About 1 second in verification mode
Output	Flexible choice of templates, images, quality metrics and diagnostic information
Voice Indication	Flexible feedback messages
Operating Temperature	32°F – 122°F (0°C – 50°C)
Storage Temperature	4°F – 140°F (-20°C – 60°C)
Humidity	0% - 95% Non-condensing

KaloVision Inc.
2909 Duncan Ave.
Clovis, CA 93611

Tel/Fax: 559-348-9489
peter@kalovision.com
www.kalovision.com